



Paint for asbestos-
cement roofs

Roofcryl color

Type of product: Flexible acrylic copolymer based-emulsion paint, especially formulated for the renovation of asbestos-cement roofs.

Characteristics: AFNOR classification: family I class 7b2

- Density: 1.15 +/-0.1
- Viscosity Cone | Plate 10.000sec: 0.9 dPa.s (a 20°C)
- Drying at 20°C: After elimination of all dust: 45 minutes
- After elimination of all adhesives: 1.30 h.
- Recoverable: 4 h.
- Gardner brilliance 60°: 25-30

Moreover, this product enjoys the following characteristics:

- Absence of toxicity
- Non-inflammable
- Storage stability: 1 year (protect from freezing).

Advantages: The product is produced entirely in aqueous phase. Excellent powers of impregnation.

Application: **Preparation of the supports:**
The supports must be:
Clean and proper.

- Perform high-pressure cleaning.
- Apply anti-moss

Application:

A. By airless gun

- Dilute with +/- 10% water.
- Apply in 2 cross coats "wet on wet".

B. By brush or roller

- Roofcryl is ready to use, for application by brush or roller.
- Apply 2 coats at a minimum of 4h interval.

Yield: +/- 200 gr/m² per coat.

Colour: Slate gray